



**INSTALLATION INSTRUCTIONS FOR 2013.5-2014
DODGE 3500 4WD
BRAKE LINE KIT
PART NUMBER 74BL**

Requires the following parts for a complete installation:

- **P/N 74BL**

WARNING!!! READ AND UNDERSTAND ALL INSTRUCTIONS BEFORE PROCEEDING. MAKE SURE THAT YOU HAVE ALL TOOLS AND PARTS BEFORE BEGINNING THE INSTALLATION.

GENERAL NOTES:

1. THIS SYSTEM SHOULD ONLY BE INSTALLED BY A PROFESSIONAL.
2. Compare all contents of the boxes to the parts list before starting to insure all components are included.
3. Prior to installing the suspension system, inspect the vehicle's suspension components, alignment, and frame for damage, corrosion, or cracks. Correct any worn or damaged parts before beginning install.
4. Always wear safety glasses during installation.
5. Estimated time to install this system is 1 hour.
6. Check off the step number at the beginning of each step when you finish it. Then when you stop during the installation, it will be easier to find where you need to continue from.

<u>74BL KIT</u>	<u>PARTS LIST INCLUDED IN KIT</u>
LEFT REAR BRAKE LINE	1
RIGHT REAR BRAKE LINE	1
8MM REAR BRAKE LINE BOLTS	2
8MM REAR BRAKE LINE LARGE WASHERS	2
8MM REAR BRAKE LINE LOCK NUTS	2
FRONT BRAKE LINES	2
ZIP TIES	8

INSTALLATION OF FRONT KIT

- a) Remove factory brake lines from their mounts just inside the frame rail and the connection just above the radius arm. Loosen ABS lines and leave loose for now. Also loosen from axle 4WD wiring. Retain brake line spring clips for reuse.
- b) Install new braided brake lines, reuse spring clips to secure them.
- c) Use included zip ties to properly secure lines in place.

INSTALLATION OF REAR KIT

- a) Remove both rear rubber brake lines from their upper and lower mounts. Retain upper clips for later use. Loosen ABS wiring and leave loose for now.
- b) Install new longer braided rear brake lines. Be sure to put the proper one on the proper side. The upper threads are a different size. Install clips to secure top and using two 8mm bolts, large washers, and lock nuts install bottom into factory mount bracket as shown.
- c) Use included zip ties to properly secure lines in place.



Limited Lifetime Warranty

Revtek Suspension products are warranted to be free from material and workmanship defects for as long as the original retail purchaser owns the vehicle upon which such products were originally installed (proof of purchase required). The consumer will be responsible for removing from the vehicle and returning any defective item, freight prepaid, and for reinstallation. This warranty is non-transferable. Revtek Suspension's limit of liability under this warranty is to repair or replace the product at Revtek Suspension's option. Consequential costs such as, but not limited to labor fees, loss of use, loss of time or freight charges are not covered. Any product that has been abused, altered incorrectly installed, or used in competition is not covered. Product finish is excluded from this warranty. Items that are subject to wear are not considered defective when worn and are not covered. The warranty is void if the "Warning to Driver" decal is not properly displayed on the vehicle. No other warranties are expressed or implied. We reserve the right to make changes in design, materials, and specifications without prior notice.

This warranty gives you specific legal rights and you may also have other rights which may vary from state to state. Some states do not allow limitations on how long an implied warranty lasts or allow the exclusion or limitation of incidental or consequential damages, the above limitation or exclusion may not apply to you.

Other than stated above, there are no warranties.

SELLER DISCLAIMS ANY IMPLIED WARRANTY OF MERCHANTABILITY

SELLER DISCLAIMS ANY IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE

This warranty to be free from material and workmanship defects shall not apply to any product which has been improperly installed modified or customized and does not apply to any components used for racing purposes or racing type activities.

To make a claim under this warranty to be free from material and workmanship defects, contact Revtek Suspension about the problem prior to removing any parts from the vehicle. If it appears that the part is warrantable, you will be given a Return Authorization (RA) number and asked to return the part freight prepaid. If the part is found to be warrantable, it will be repaired or replaced and returned to you. All freight charges are the customer's responsibility. If a replacement part is needed before the part in question can be returned, you must first purchase the replacement part. Then if the part in question is deemed warrantable, you will be credited / refunded by the authorized Revtek dealer the part was purchased from.

Shocks and bushings are considered to be wear items. As such, they will be covered for a period of 12 months from the original installation. Any failure outside of 12 months will be considered typical wear.

REVTEK SUSPENSION, LLC 503-659-1650
15800 SE Piazza Ave #104, Clackamas OR 97015